

標準クレーン台船搭載時定格荷重表

■主ブーム定格荷重表

単位:荷重(トン) 角度(度)

| ブーム長 (m)<br>作業半径 (m) | 13   |      | 16   |      | 19   |      | 22   |      | 25   |      | 28   |      | 31   |      |
|----------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
|                      | 荷重   | 角度   | 荷重   | 角度   | 荷重   | 角度   | 荷重   | 角度   | 荷重   | 角度   | 荷重   | 角度   | 荷重   | 角度   |
| 4.0                  | 60.0 | 78.5 |      |      |      |      |      |      |      |      |      |      |      |      |
| 4.5                  | 55.0 | 76.0 | 54.9 | 79.0 |      |      |      |      |      |      |      |      |      |      |
| 5.0                  | 49.0 | 74.0 | 48.9 | 77.0 | 48.8 | 79.0 |      |      |      |      |      |      |      |      |
| 5.5                  | 42.6 | 71.5 | 42.5 | 75.0 | 42.4 | 77.5 | 42.3 | 79.0 |      |      |      |      |      |      |
| 6.0                  | 37.0 | 69.0 | 38.9 | 73.0 | 36.8 | 76.0 | 36.7 | 78.0 | 36.6 | 79.5 |      |      |      |      |
| 7.0                  | 29.4 | 64.0 | 29.3 | 69.5 | 29.2 | 73.0 | 29.1 | 75.0 | 29.0 | 77.0 | 28.9 | 78.5 | 28.8 | 79.5 |
| 8.0                  | 24.5 | 59.0 | 24.4 | 65.5 | 24.3 | 69.5 | 24.2 | 72.5 | 24.1 | 74.5 | 24.0 | 76.5 | 23.9 | 77.5 |
| 9.0                  | 20.8 | 54.0 | 20.7 | 61.5 | 20.6 | 66.0 | 20.5 | 70.0 | 20.4 | 72.0 | 20.3 | 74.0 | 20.2 | 76.0 |
| 10.0                 | 18.0 | 48.0 | 17.9 | 57.0 | 17.8 | 63.0 | 17.7 | 67.0 | 17.6 | 70.7 | 17.5 | 72.0 | 17.4 | 74.0 |
| 12.0                 | 14.0 | 34.0 | 13.9 | 48.0 | 13.8 | 56.0 | 13.7 | 61.0 | 13.6 | 65.0 | 13.5 | 67.5 | 13.3 | 70.0 |
| 14.0                 |      |      | 11.2 | 37.0 | 11.1 | 48.0 | 11.0 | 55.0 | 10.9 | 59.5 | 10.8 | 63.0 | 10.7 | 66.0 |
| 16.0                 |      |      |      |      | 9.5  | 39.0 | 9.4  | 48.0 | 9.3  | 54.0 | 9.2  | 58.5 | 9.1  | 62.0 |
| 18.0                 |      |      |      |      |      |      | 8.0  | 40.5 | 7.9  | 48.0 | 7.8  | 53.5 | 7.7  | 57.5 |
| 20.0                 |      |      |      |      |      |      | 6.9  | 31.5 | 6.8  | 41.5 | 6.7  | 48.0 | 6.6  | 53.0 |
| 22.0                 |      |      |      |      |      |      |      |      | 6.0  | 34.0 | 5.9  | 42.0 | 5.8  | 48.0 |
| 24.0                 |      |      |      |      |      |      |      |      |      |      | 5.2  | 35.5 | 5.1  | 43.0 |
| 26.0                 |      |      |      |      |      |      |      |      |      |      |      |      | 4.5  | 37.0 |